



The Chevin S4120L is designed to meet every standard for distributed sound systems with isolated 50V, 70V and 100V outputs. Its controlled cooling provides quiet operation. Powder coated steel face plates and heavy-duty steel chassis reflect the manufacturing quality within. It carries the CE approval for world-wide use.

POWER

4 x 120 Watt



OUTPUTS

4 x 50 Volt
4 x 70 Volt
4 x 100 Volt



COOLING

variable speed fan



CONNECTORS

Inputs
XLR –balanced



Outputs

Phoenix connectors

Technical specification

Power output (1kHz at 1.0%THD)	4 x 120 W	
Input sensitivity	1V	
Input impedance	20 kΩ	Balanced
THD	1 kHz / - 3dB	< 0,05 %
Frequency response	- 3 dB	20Hz - 20kHz
S/N Ratio	> 100 dB	
“A” weighted	> 104 dB	
Output [V]	50 / 70 / 100	

Protection:
signal limiter, short circuit, DC, overload, load-mismatch

Cooling: variable speed fan

Inputs:
- balanced XLR female for every channel

Indicators:
- ON green LED
- SIGNAL green LED for every channel
- PROTECT red LED

Controls:
- power switch On / Off
- volume - level control for all channels

Power Requirements AC ~ 230V / 120V 50 / 60 Hz

Rack 2U
Dimensions 483 x 88 x 360 mm
Weight 13,6 kg

