



Compact power amplifier S 480LP with passive cooling is designed for using in distributed sound systems with isolated 50V , 70V and 100V outputs.

POWER 400 Watt



OUTPUTS 50 Volt 70 Volt 100 Volt



CONVECTION Cooling



CONNECTORS Inputs XLR –balanced RCA



Output Terminal block



AUTOMATIC PROTECTION

Technical specification

Power output (1kHz at 1,0%THD)	400 W	
Input sensitivity	1V	
Input impedance	20 kΩ	Balanced
THD	1 kHz	< 0,07 %
Frequency response	- 3 dB	20Hz - 20kHz
S/N Ratio	> 100 dB (> 104 dB "A")	
Output [V]	50 / 70 / 100	

Features:

- automatic signal limiter
- thermal protection & automatic idling circuitry to insure stability and reliability against over-current and overheating, thermal protection circuitry is provided
- convection cooling (fan assisted in extreme situations)

Inputs:

- balanced XLR male + female
- unbalanced RCA left + right

Indicators:

- ON green LED
- SIGNAL green LED
- PEAK red LED

Controls:

- Power switch On / Off
- volume level adjustment control

Power Requirements	AC ~ 230V / 120V	50 / 60Hz
Rack	2U	
Dimensions	485 x 88 x 297 mm	
Weight	12 kg	

