



FANE

FPT-150 Supertweeter Options

FANE INTERNATIONAL LTD.

Sovereign House
Gilcar Way
Wakefield Europort
Castleford WF10 5QS
England
TEL +44 (0) 1924 224618
FAX +44 (0) 1924 899166
info@fane-international.com
www.fane-international.com

Horn Specifications

Dispersion	100 x 50l
Dimensions	7.5" x 4.5"/191mm x 114mm
Cut-out	6.7" x 3.4"/170mm x 86mm
Depth	4.5"/114.3mm
Weight	2lbs/909g

Horn used on FPT-50 driver.



FPT-50 Driver

Electro Mechanical Specifications

Throat Size	1", 25.4mm
Nominal Impedance*	8 ohms
Power Rating	45W @ 3.5kHz, 85Wrms @5kHz
Resonance	2.5kHz
Usable Frequency Range	3.5Hz - 20kHz
Recommended Crossover	3.5kHz
Sensitivity	105dB
Magnet Weight	7.75oz, .22kg
Voice Coil Diameter	1.0" / 25.4mm
Re	6.3
Le	1.5mH

Mounting information

Use with APT3 adaptor for 1 3/8" 18 NEF ext.

Overall Diameter	2.75", 70mm
Depth	1.57", 40mm
Weight	1.5 lbs, 682 kg.

Materials of Construction

Diaphragm Material	Phenolic
Polarity	A Negative voltage at the red terminal Causes a positive pressure at the output of the device

Please inquire about alternative impedances.

