



**FANE**

# FPT-80 Supertweeter Options

**FANE INTERNATIONAL LTD.**  
Sovereign House  
Gilcar Way  
Wakefield Europort  
Castleford WF10 5QS  
England  
TEL +44 (0) 1924 224618  
FAX +44 (0) 1924 899166  
info@fane-international.com  
www.fane-international.com



## Horn Specifications

Dispersion	80° Conical
Dimensions	3.4" x 3.4"/87mm x 87mm
Cut-out	3.15"/80mm
Depth	2.9"/73.6mm
Weight	1.6lbs/727g

Horn used on FPT-50 driver.



**FPT-50** Driver

## Electro Mechanical Specifications

Throat Size	1", 25.4mm
Nominal Impedance*	8 ohms
Power Rating	45W @ 3.5kHz, 85Wrms @5kHz
Resonance	2.5kHz
Usable Frequency Range	3.5Hz - 20kHz
Recommended Crossover	3.5kHz
Sensitivity	105dB
Magnet Weight	7.75oz, .22kg
Voice Coil Diameter	1.0" / 25.4mm
Re	6.3
Le	1.5mH

## Mounting information

Use with APT3 adaptor for 1 3/8" 18 NEF ext.

Overall Diameter	2.75", 70mm
Depth	1.57", 40mm
Weight	1.5 lbs, 682 kg.

## Electro Mechanical Specifications

Diaphragm Material	Phenolic
Polarity	A Negative voltage at the red terminal Causes a positive pressure at the output of the device

Please inquire about alternative impedances.

